

Video Security



F03Z2.710DC-NFS

F1.0/3-8mm DC Lens/var. Focal Length
No Focus Shift, 1/3" CS Mount

Art-Nr. 43238



Features

Suitable for 1/3" and 1/4" Colour and B&W Cameras
No-Focus-Shift from Visible to Near IR Light Range
Variable Focal Length
Aspherical Lens Elements
CS Mount

High Standard of Optical and Mechanical Quality
Without Built-in Auto Iris Amplifier
With 4-pin Connector
Adjustable Slip-ring Mount for Cable Positioning

Specifications

Focal length (f)	3.0-8mm
Aperture range (F)	F1.0-F240
Lens mount	CS
Nominal format size	1/3"
Flange focal length	12.5mm
Horizontal angle of view at nominal format size	90.8°-36.2°
Minimum object distance (M.O.D.)	0.2m
Focus constant range	+0.03mm at f3.0mm; +0.03mm at f8.0mm (Focus deviation at switch-over to IR light at 880nm)
Screw-in depth	5.0mm
Filter screw size	-
Cable length	Approx. 20cm
Slip-ring mount	340°-360° Variable adjustment range
Iris control system	Galvanometer
4-pin plug	Standard
Temperature range	-20°C to +50°C
Dimensions (LxDxH)	See drawing
Weight	Approx. 40g

Accessories of

91892 / VKC-1319IR12-24	1/3" Day/Night Camera with Switchable IR
91836 / VKC-139/IR-SU	1/3" Day/Night Camera with Sens-up
92486 / CG-311PA1V	1/3" Day/Night Camera with Switchable IR
91937 / VKC-1319/IR	1/3" Day/Night Camera with Switchable IR
91418 / ENC-1001P	1/3" Network Colour Camera w. CS Mount
91943 / VKC-1323/IR-12V	1/3" Day/Night Camera with Switchable IR

