

# VKC-1331

Home | Security | Cameras | Plug & Play

VKC-1331  
1/3" Cylindric Camera, Colour, 3.6mm, 380TVL,  
12VDC

**Art-Nr. 91978**



## Main Features

Weatherprotected CCD colour cylindric camera  
19mm outside diameter only  
1/3" Super HAD CCD  
Resolution of 380 horizontal lines  
Automatic shutter control (ESC)  
H & V aperture (APC)

Automatic white balance (AWB)  
Internal synchronization  
Supply voltage: 12VDC  
Weatherproof aluminium housing  
Mounting stand with swivel head  
Option: version with 170° door view lens

## Specifications

System	colour
Video standard	PAL
Sensor size	1/3"
Imager	CCD, Sony Super HAD Interline Transfer
Active picture elements	440,000, 752(H) x 582(V)
Synchronization	internal
Signal-to-noise ratio	48dB
Gamma correction	0.45
Horizontal resolution	380 TVL
Sensitivity (at 50% video signal)	0,64 Lux, at F1.2 (measured)
Automatic electronic shutter (ESC)	1/50 ~ 1/100,000sec.
Low speed shutter	no
Automatic gain control (AGC)	yes

# VKC-1331

(Continuation Specifications)

Digital Noise Reduction (DNR)	no
White balance	automatic (2100 - 8000K)
Backlight compensation	no
Wide Dynamic Range (WDR)	no
IR cut filter	standard
Video outputs	composite (CVBS)
Lens type	fixed focal length
Lens	F2.0/3.6mm
Focal length	3,6 mm
PTZ support	no
Digital zoom	no
Horizontal angle of view	69°
Iris control	no
MOD (Minimum object distance)	0,1 m
Filter screw size	not available
Illumination	no
Activity detection	no
Serial interfaces	no
Cable connection	Wiring for video and voltage supply made, accessible from outside (approx. 0.5m long, Video: BNC jack 12/24V input: for DC plug 2.1/5.5mm)
Temperature range (operation)	-10°C ~+50°C
Housing material	aluminium
Housing	outdoor
Integrated wall mount	no
Hidden cable management	no
Sunshield	no
Window heater	no
Clear Shield	no
Colour (housing)	black
Vandalism resistant	no
Protection rating	IP67
Alarm inputs	-
Alarm outputs	-
Supply voltage	12VDC
Power consumption	approx. 1.7watts
Dimensions (HxWxD)	19x19x54,7 mm
Weight	approx. 80g (incl. stand)
Certificates	CE

## Optional accessories

## VKC-1331

70535	VT-PS12DC-8	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug
70495	VT-PS12DC-7	Plugable PSU w. Cont. & UK Mains plug-in 100-240VAC/12VDC-1.25A, Regulated
77773	VT-PS12DCDT1	PSU 12VDC/1.0A, Regulated, Desktop Version, 1.8m Cables each w. open ends

SLD Security & Communications  
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England  
Phone +44.1483225633 · Fax +44.1483225634  
sales@sld.co.uk · www.sld.co.uk

