

## Fixed Dome & Covert Cameras

1/3" Colour Camera in PIR-Housing with  
3,7mm Lens, 12VDC, 340TVL, 4,44Lux

EDP-No.: 91813

### VKC-149/PIR

- For Wall Mount
- Resolution of 380 Horizontal Lines
- Built-in Pinhole Lens F2.0/3.7 mm
- Electronic Shutter Control (ESC)
- Internal Synchronization
- Easy Installation
- Supply Voltage: 12 VDC



### Specifications:

Imager	1/4" Sony Super HAD Interline Transfer CCD
System	CCIR/PAL
Synchronization	Internal
Sensitivity at 50% video signal	2.5 Lux at F2.0 (VT measurement result)
Horizontal resolution	380 TV lines
Picture elements	Approx. 290,000 (H) 512 x (V) 582
Electronic shutter (ESC)	1/50 to 1/100,000 sec. (automatic)
Lens	F2.0/3.7 mm Pinhole
Horizontal angle of view	Approx. 55°
Video output	1 Vp-p, CVBS, 75 ohms
Mounting	Wall mount (bracket included)
Supply voltage	12 VDC +/-10 %
Power consumption	Approx. 1.3 watts
Temperature range	-10° to +50°C
Housing	Plastic
Colour	Light grey
Dimensions (HxWxD)	110x70x50 mm(w./o. bracket)
Weight	Approx. 100 g
Special features	Build-in microphone with pre-amplifier and PIR sensor function

---

<b>Accessories</b>	
<b>EDP No. / Type</b>	<b>Description</b>
<b>77779 VT-PS12DC-UK</b>	Plugable PSU 12VDC-500mA, stabilized with UK mains plug, open DC lead
<b>70443 VT-PS12DC-4</b>	Power Supply 230VAC/12VDC(500mA), stabilized, with DC Plug