

Switcher and Amplifier

Video Signal Distributor 1 Inp., 4 Outp.
in Housing, 230VAC

EDP-No.: 75101

VDA-4A

- 1 Input
- 4 Outputs
- Video Bandwidth: 10 MHz (+/-3 db)
- Signal-to-noise Ratio: >55 db
- Integrated Signal Pre-Equalization (HF Gain)
- Integrated Signal Pre-Amplification (Linear Gain)
- Supply Voltage: 230 VAC / 50 Hz



Specifications:

Video input	1.0 to 2.0 Vp-p, (C)VBS, 75 ohms, BNC
Video outputs	4x 1.0 to 2.0 Vp-p, (C)VBS, 75 ohms, BNC
Video signal bandwidth	0 to 10 MHz +/-3db
Signal-to-noise ratio	>55db
Signal pre-equalization range (HF gain)	0 to 6.0 db stepless adjustable (common for all outputs)
Distributor configuration	1 input to 4 outputs
Signal pre-amplification range (linear gain)	0 to 6.0 db stepless adjustable (common for all outputs)
Internal adjustments	1 Potentiometer each for the stepless adjustment of the linear and HF gain
Tilt	</= 1 % at 50 Hz
Supply voltage	230 VAC / 50 Hz
Power consumption	Approx. 3.0 W
Temperature range	0°C to +50°C
Housing	Steel metal
Colour	Pantone Coolgray 1C
Dimensions (HxWxD)	44x108x135 mm
Weight	Approx. 600 g