

POE576U-16AT

Home | Security | IP Cameras | Accessories

POE576U-16AT

Ultra PoE Midspan, 16 Ports, 33.6W, Gigabit, USB,

0° to +40°C, 100-240VAC

Art-Nr. 170052



SLD Security & Communications

Main Features

Compliant with the IEEE802.3at standard

Transient voltage and over temperature protection

Overcurrent and short circuit protection

Gigabit compatible (10/100/1000Base-T)

Diagnostic LEDs

USB port for diagnostics and manual port control

NIC Network Interface Card

Full power of 538W (33.6W per port)

GUI Graphical User Interface

Cisco Legacy detection

Voice-over-IP, Access point, Security application

19" rack mounting kit included

Specifications

Switch type	PoE midspan
Ports	16
Power/port	33,6W
Remote control	no
Voltage input	100 - 240VAC
Output voltage	n/a
PoE standard	PoE+ (IEEE802.3at)
Cisco Legacy	yes
Gigabit	yes
Resistive power discovery	yes
Local Control	USB
Temperature range (operation)	0°C ~+40°C
19" Rack mountable	yes

SLD Security & Communications
The Old Forge, Ockham Lane, Ockham, Surrey GU236PH England
Phone +44.1483225633 · Fax +44.1483225634
sales@sld.co.uk · www.sld.co.uk

